


C O P P E R R O D



COPPER CITY

COPPER INDUSTRIES COMPANY

DUBAI, UAE

SALES@COPPERCITYCO.COM

W W W . C O P P E R C I T Y C O . C O M



Oxygen free Up-cast copper rod

Diameter(mm)	8	12	16	20	25
Tolerance	± 0.38	± 0.38	± 0.38	± 0.51	± 0.51
Coil weight(KG)	2500 to 3500				

Standards:

- ASTM B49

Composition:

- Oxygen free copper (max 10ppm)

Physical specification

- Electrical conductivity: 58ms/m
- IACS: Min 100%
- Tensile strength: 170 N/mm²
- Density: 8.90 KG/dm³
- Elongation: Min 30%
- Drawability: to 0.05 mm
- Resisitivity (20c°): Max 0.017241 Ωmm²/m

Application:

- Cable manufacturer, enamelled wire manufacturing

Packing:

- Pallet dimensions: 1650*1650*150 mm
- Internal coil diameter: 900 mm
- external coil diameter 1800 mm
- * The surface of oxygen-free copper rod is smooth and clean without cracks and micro holes.



COPPER CITY

COPPER INDUSTRIES COMPANY

Address: Office 1419, Regal Tower, Business Bay, Dubai
 Call and WhatsApp: +971 50 362 8511 | Phone: +971 4 566 3225
 Email: sales@coppercityco.com